STRONGVIEW & STRONGVIEW L

MOTORIZED SCREENS

Standard Format: 13' – 1" (4m) to 18' – 6" (5.6m) image width Large Format: 18' – 7" (5.7m) to 25' (7.62m) image width

Custom designed and fabricated motorized screen.

Featuring an elegant design and a silent operation system using a heavy duty tubular motor. Nylon side tab tensioners ensure a smooth, wrinkle free projection screen. Available with most of our perforated or non-perforated surfaces.



FEATURES

- UL/cUL approved, ½ HP tubular motor,120V - 5amp
- Separate control box with wireless module
- Truss dimensions:
 Standard format

Height: 14" Depth: 10-3/4" (35.5cm x 27.3cm) Large format

Height: 14" Depth: 12" (35.5cm x 30.48cm)

- ▶ 1/8" (3.2 mm) thick mat black aluminum composite panel with polyethyline core (add 1/8" (3.2mm) to truss height and 1/4" (6.35mm) to truss depth)
- ▶ Rigid 1" x 1" (25.4mm x 25.4mm) steel tubing head truss assembly
- Nylon side tension tab cable
- ▶ Up to 1:1 format ratio

- Custom black PVC masking borders
- Handheld RF wireless remote control included (2)
- Low voltage control trigger (Down/Stop/Up) on terminal strip
- ▶ 1 x 120V male 'U'-ground connector
- Standard 2 year warranty

OPTIONS

- ▶ 220V 240V operation
- Wired wall mount key pad remote control (VMR4)
- CUL/CSA twist lock male connector (to be specified)
- Adaptable rigging hardware (to be specified)
- Perforated, non-perforated front or rear projection surfaces (non-coated)
- Extended 3 year warranty

