

# STRONGVIEW XL

## MOTORIZED SCREEN

### Up to 36' – 6" (11.12 m) in image width

The **STRONGVIEW XL** is customized to fit your venue requirements. The sleek motorized screen rolls up and down quietly thanks to a silent and reliable operation system. Steel cables and side tab tensioners prevent wrinkles and creases, resulting in a smooth, wrinkle-free screen surface. The system is compatible with all our non-coated screens.



### FEATURES

- ▶ CSA certified 1/2 HP motor with brake system, ramp-up and ramp-down operation, 120V - 6.5amp
- ▶ 1" x 1" (25,4mm x 25,4mm) rigid steel tubing head truss assembly
- ▶ Nylon side tension tabs
- ▶ Heavy duty 6" (152,4mm) diameter aluminum tube
- ▶ Custom black PVC masking borders
- ▶ Head truss protected by 3mm matte black expanded PVC cover panels
- ▶ Handheld RF wireless remote control included (2)
- ▶ Machined aluminum drums with cable winding guards
- ▶ 3/16" (4,8mm) tensioned steel winding cables
- ▶ Separate control box with wireless module
- ▶ Low voltage control trigger (Down/Stop/Up) on terminal strip
- ▶ 2 x 110V male 'U'-ground connectors (electric +electronics)

### OPTIONS

- ▶ 1/8" (3.2 mm) thick mat black aluminum composite panel with polyethylene core (add 1/8" (3,2mm) to truss height and 1/4" (6,35mm) to truss depth)
- ▶ 220V – 240V operation
- ▶ Wired wall mount key pad remote control (VMR4)
- ▶ CUL/CSA twist lock male connector (to be specified)
- ▶ Adaptable rigging hardware (to be specified)
- ▶ Perforated, non-perforated front or rear projection surfaces (non-coated)
- ▶ Independent masking system upgrade